

Model: C1400 N5C
Frequency: 50 Hz
Fuel Type: Low BTU (12.7:1)
Emissions Performance NOx: 500 mg/Nm³
LT Water Inlet Temperature: 50°C (122°F)
HT Water Outlet Temp: 90°C (194°F)

Generator set data sheet
1400kW continuous

Our energy working for you.™



**Power
Generation**

Measured Sound Performance Data Sheet:	MSP-1067
Prototype Test Summary Data:	PTS-287
Generator Set Outline Drawing:	A029U550 Normal Duty Air Filtration A029E093 Heavy Duty Air Filtration

Fuel Consumption (ISO3046/1)	See Note	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
Fuel Consumption (LHV) ISO3046/1, kW (MMBTU/hr)	2,3,6,9	3399 (11.61)	3089 (10.55)	2652 (9.06)	1931 (6.59)
Mechanical Efficiency ISO3046/1, percent	2,9,6	42.4%	42.0%	40.9%	37.7%
Electrical Efficiency ISO3046/1, percent	2,9,11	41.2%	40.8%	39.6%	36.3%

Engine	
Engine Manufacturer	Cummins
Engine Model	QSK60G
Configuration	V16
Displacement, L (cu.in)	60 (3671)
Aspiration	Turbocharged (1)
Gross Engine Power Output, kWm (hp)	1442 (1933)
BMEP, bar (psi)	19.4 (281.3)
Bore, mm (in)	159 (6.26)
Stroke, mm (in)	190 (7.48)
Rated Speed, rpm	1500
Piston Speed, m/s (ft/min)	9.5 (1870)
Compression Ratio	12.7:1
Lube Oil Capacity, L (qt)	380 (400)
Overspeed Limit, rpm	1875
Full Load Lubricating oil consumption, g/kWe-hr (g/hp-hr)	0.15 (0.11)

Fuel	
Gas supply pressure to engine inlet, bar (psi) ⁶	0.20 (2.9)
Minimum Methane Index	75

Starting System(s)	
Electric starter voltage, volts	24
Minimum battery capacity @ 40 deg.C (104 deg.F), AH	720
Air Starter Pressure, barg (psig)	NA
Air Starter Flow Nm ³ /s (scfm)	NA

Genset Dimensions (see note 1)	
Genset Length, m (ft)	5.12 (16.8)
Genset Width, m (ft)	2.23 (7.30)
Genset Height, m (ft)	2.77 (9.08)
Genset Weight (wet), kg (lbs)	15450 (33,990)

	See Notes	100% of Rated Load	90% of Rated Load	75% of Rated Load	50% of Rated Load
Energy Data					
Continuous Generator Electrical Output kWe @ 1.0 pf	2,6,11	1400	1260	1050	700
Total Heat Rejected in LT Circuit, kW (MMBTU/h)	4	96 (0.33)	86 (0.29)	74 (0.25)	53 (0.18)
Total Heat Rejected in HT Circuit, kW (MMBTU/h)	4	765 (2.61)	676 (2.31)	527 (1.80)	389 (1.33)
Unburnt, kW (MMBTU/h)	12	67 (0.23)	62 (0.21)	52 (0.18)	40 (0.14)
Heat Radiated to Ambient, kW (MMBTU/h)	12	219 (0.75)	199 (0.68)	171 (0.58)	128 (0.44)
Available Exhaust heat to 105C, kW (MMBTU/h)	4	876 (2.99)	821 (2.80)	758 (2.59)	588 (2.01)
Intake Air Flow					
Intake Air Flow Mass, kg/s (lb/hr)	3	2.09 (16550)	1.89 (14970)	1.58 (12510)	1.11 (8790)
Intake Air Flow Volume, m ³ /s @ 0°C (scfm)	3	1.62 (3620)	1.46 (3260)	1.22 (2720)	0.86 (1920)
Maximum Air Cleaner Restriction Below 35C, mmHG (in H ₂ O)		28 (15.0)	23 (12.1)	16 (8.4)	7 (3.7)
Maximum Air Cleaner Restriction Above 35C, mmHG (in H ₂ O)		19 (10.0)	15 (7.9)	10 (5.5)	4 (2.4)
Exhaust Air Flow					
Exhaust Gas Flow Mass, kg/s (lb/hr)	3	2.17 (17190)	1.96 (15520)	1.64 (12990)	1.15 (9110)
Exhaust Gas Flow Volume, m ³ /s (cfm)	3	4.51 (9550)	4.15 (8790)	3.63 (7690)	2.68 (5670)
Exhaust Temperature After Turbine, °C (°F)	5	461 (862)	475 (887)	509 (948)	550 (1022)
Max Exhaust System Back Pressure, mmHG (in H ₂ O)	13	37.3 (20.0)	30.6 (16.4)	20.9 (11.2)	9.7 (5.2)
HT Cooling Circuit					
HT Circuit Engine Coolant Volume, l (gal)		181 (48)	181 (48)	181 (48)	181 (48)
HT Coolant Flow @ Max Ext Restriction, m ³ /h (gal/min)		70 (310)	70 (310)	70 (310)	70 (310)
Maximum HT Engine Coolant Inlet Temp, °C (°F)	7	79 (174)	81 (178)	83 (181)	84 (183)
HT Coolant Outlet Temp, °C (°F)	7	90 (194)	90 (194)	90 (194)	90 (194)
Max Pressure Drop in External HT Circuit, bar (psig)		1.0 (15)	1.0 (15)	1.0 (15)	1.0 (15)
HT Circuit Maximum Pressure, bar (psig)		5.0 (73)	5.0 (73)	5.0 (73)	5.0 (73)
Minimum Static Head - Pump Inlet, bar (psig)		0.5 (7)	0.5 (7)	0.5 (7)	0.5 (7)
LT Cooling Circuit					
LT Circuit Engine Coolant Volume, l (gal)		34 (9)	34 (9)	34 (9)	34 (9)
LT Coolant Flow @ Max Ext Restriction, m ³ /h (gal/min)		23 (101)	23 (101)	23 (101)	23 (101)
Maximum LT Engine Coolant Inlet Temp, °C (°F)	8	50 (122)	50 (122)	50 (122)	50 (122)
Max Pressure Drop in External LT Circuit, bar (psig)		1.0 (15)	1.0 (15)	1.0 (15)	1.0 (15)
LT Circuit Maximum Pressure, bar (psig)		5.0 (73)	5.0 (73)	5.0 (73)	5.0 (73)
Minimum Static Head - Pump Inlet, bar (psig)		0.5 (7)	0.5 (7)	0.5 (7)	0.5 (7)
Emissions					
NO _x Emissions, mg/Nm ³ @5% O ₂ (g/hp-h)	14	500 (1.00)	500 (1.00)	500 (1.00)	500 (1.00)

Genset De-rating

Altitude and Temperature Derate Multiplication Factor

Barometer		Altitude		Table A *									
In Hg	mbar	Feet	Meters	Derate Multiplier with Grid Parallel Operation									
20.7	701	9843	3000	0.75	0.75	0.71	0.68	0.61	0.53	-	-	-	
21.4	723	9022	2750	0.79	0.78	0.73	0.70	0.63	0.54	-	-	-	
22.1	747	8202	2500	0.82	0.81	0.76	0.72	0.64	0.55	-	-	-	
22.8	771	7382	2250	0.86	0.84	0.80	0.74	0.65	0.55	-	-	-	
23.5	795	6562	2000	0.89	0.88	0.83	0.78	0.67	0.56	-	-	-	
24.3	820	5741	1750	0.93	0.91	0.86	0.81	0.68	0.56	-	-	-	
25.0	846	4921	1500	0.96	0.94	0.90	0.85	0.69	0.57	-	-	-	
25.8	872	4101	1250	1.00	0.97	0.93	0.89	0.71	0.57	-	-	-	
26.6	899	3281	1000	1.00	1.00	0.97	0.93	0.72	0.58	-	-	-	
27.4	926	2461	750	1.00	1.00	1.00	0.96	0.74	0.58	-	-	-	
28.3	954	1640	500	1.00	1.00	1.00	1.00	0.75	0.59	-	-	-	
29.1	983	820	250	1.00	1.00	1.00	1.00	0.75	0.59	-	-	-	
29.5	995	492	150	1.00	1.00	1.00	1.00	0.75	0.59	-	-	-	
30.0	1012	0	0	1.00	1.00	1.00	1.00	0.75	0.59	-	-	-	
				°C	20	25	30	35	40	45	50	55	60
				°F	68	77	86	95	104	113	122	131	140
				Air Filter Inlet Temperature									

* Based on SAE standard ambient pressure vs. altitude. Assumes LT return temperature is 10C above air filter inlet.

Heat Rejection Factor (altitude and ambient) for HT and LT Circuits

Barometer		Altitude		Table B									
In Hg	mbar	Feet	Meters	Multiplier for HT & LT Heat Rejection vs Alt & Temp.									
20.7	701	9843	3000	1.06	1.10	1.11	1.13	1.14	1.15	1.17	1.18	1.19	
21.4	723	9022	2750	1.05	1.09	1.10	1.12	1.13	1.14	1.15	1.17	1.18	
22.1	747	8202	2500	1.04	1.08	1.09	1.10	1.12	1.13	1.14	1.16	1.17	
22.8	771	7382	2250	1.03	1.07	1.08	1.09	1.11	1.12	1.13	1.14	1.16	
23.5	795	6562	2000	1.02	1.06	1.07	1.08	1.09	1.11	1.12	1.13	1.15	
24.3	820	5741	1750	1.01	1.04	1.06	1.07	1.08	1.10	1.11	1.12	1.14	
25.0	846	4921	1500	0.99	1.03	1.05	1.06	1.07	1.09	1.10	1.11	1.12	
25.8	872	4101	1250	0.98	1.02	1.04	1.05	1.06	1.07	1.09	1.10	1.11	
26.6	899	3281	1000	0.97	1.01	1.02	1.04	1.05	1.06	1.08	1.09	1.10	
27.4	926	2461	750	0.96	1.00	1.01	1.03	1.04	1.05	1.07	1.08	1.09	
28.3	954	1640	500	0.95	0.99	1.00	1.02	1.03	1.04	1.05	1.07	1.08	
29.1	983	820	250	0.94	0.98	0.99	1.00	1.02	1.03	1.04	1.06	1.07	
29.5	995	492	150	0.94	0.97	0.99	1.00	1.01	1.03	1.04	1.05	1.06	
30.0	1012	0	0	0.93	0.97	0.98	0.99	1.01	1.02	1.03	1.05	1.06	
				°C	20	25	30	35	40	45	50	55	60
				°F	68	77	86	95	104	113	122	131	140
				Air Filter Inlet Temperature									

Temperature & Altitude Derate

1. Determine derate multiplier vs. temperature and altitude in Table A depending upon your operating condition.
2. Assumes the LT return temperature is 10 deg C above the air filter inlet with a maximum LT temperature of 50 deg C.
3. If the LT temperature exceeds 50 deg C, consult factory for recommendations.
4. Altitude is based upon SAE standard ambient pressure vs. altitude. For low barometric conditions add 150m (500 ft) to site altitude.

LT & HT Circuit Heat Rejection Calculation

1. Determine derate multiplier vs. temperature derate per above.
2. Using the multiplier from #1 above as the percent load factor determine the Heat rejection from the previous page.
3. From Table B find the HT and LT circuit multiplier.
4. Multiply the result of step 2 by the result of step 3 to obtain the heat rejection at your altitude and temperature.

Preliminary

Alternator Data

Voltage Range	Connection Configuration	Temp Rise Degrees C	Duty ¹⁰ Cycle	Single Phase Factor	Alternator Data Sheet	Feature Code
380-440	Wye, 3 Phase	80	C	N/A	335	B703-2
380-440	Wye, 3 Phase	105	C	N/A	334	B551-2
6300-6600	Wye, 3 Phase	80	C	N/A	521	B593-2
10000	Wye, 3 Phase	80	C	N/A	521	B794-2
10500-11000	Wye, 3 Phase	80	C	N/A	521	B835-2

Continuous Rating Definition

Applicable for supplying power continuously to a constant load up to the full output rating for unlimited hours. No sustained overload capability is available for this rating. Consult authorized distributor for rating. (Equivalent to Continuous Power in accordance with ISO8528, ISO3046, AS2789, DIN6271, and BS5514).

Notes

- 1) Weights and set dimensions represent a generator set with its standard features only. See outline drawing for other configurations.
- 2) At ISO3046 reference conditions, altitude 1013 mbar (30in Hg), air inlet temperature 25°C (77°F)
- 3) According to ISO 3046/I with fuel consumption tolerance of +5% -0%
- 4) Production variation/tolerance ±10%.
- 5) With air intake at 25°C (77°F). Tolerance ± 10°F.
- 6) Based on gas LHV of 16.9 MJ/kg (19.9 MJ/scm)
- 7) Outlet temperature controlled by thermostat. Inlet temperature for reference only.
- 8) Inlet temperature controlled by thermostat, outlet temperature for reference only.
- 9) With off engine coolant pumps.
- 10) Standby (S), Prime (P), Continuous (C)
- 11) At electrical output of 1.0 Power Factor
- 12) Tolerance +/- 15%
- 13) Exhaust system back pressure is at rated load and will decrease at lower loads.
- 14) Tolerance ±10% for 500mg, ±14% for 350mg

Cummins Power Generation
 1400 73rd Avenue NE
 Minneapolis, MN 55432 USA
 Telephone: 763 574 5000
 Fax: 763 574 5298
 Web: www.cumminspower.com

Cummins Power Generation
 Manston Park, Columbus Avenue
 Manston, Ramsgate
 Kent CT12 5BF, UK
 Telephone: +44 (0) 1843-255000
 Fax: +44 (0) 1843-255902
 Email: cpg.uk@cummins.com
 Web: www.cumminspower.com



Preliminary